

(19) 世界知的所有権機関
国際事務局



(43) 国際公開日
2003 年 11 月 6 日 (06.11.2003)

PCT


(10) 国際公開番号
WO 03/090982 A1

- (51) 国際特許分類⁷: B25J 13/00, 5/00 (72) 発明者; および
(21) 国際出願番号: PCT/JP03/05450 (75) 発明者/出願人 (米国についてのみ): 竹中 透 (TAKENAKA, Toru) [JP/JP]; 〒351-0193 埼玉県 和光市 中央 1 丁目 4 番 1 号 株式会社本田技術研究所内 Saitama (JP). 松本 隆志 (MATSUMOTO, Takashi) [JP/JP]; 〒351-0193 埼玉県 和光市 中央 1 丁目 4 番 1 号 株式会社本田技術研究所内 Saitama (JP).
(22) 国際出願日: 2003 年 4 月 28 日 (28.04.2003)
(25) 国際出願の言語: 日本語
(26) 国際公開の言語: 日本語
(30) 優先権データ: 特願2002-127682 2002 年 4 月 26 日 (26.04.2002) JP (74) 代理人: 佐藤 辰彦, 外 (SATO, Tatsuhiko et al.); 〒151-0053 東京都 渋谷区 代々木 2-1-1 新宿メインタワー 16 階 Tokyo (JP).
(71) 出願人 (米国を除く全ての指定国について): 本田技研工業株式会社 (HONDA GIKEN KOGYO KABUSHIKI KAISHA) [JP/JP]; 〒107-8556 東京都 港区 南青山二丁目 1 番 1 号 Tokyo (JP). (81) 指定国 (国内): JP, KR, US.
(84) 指定国 (広域): ヨーロッパ特許 (DE, FR, GB).

[続葉有]

(54) Title: CONTROL DEVICE AND FOOTSTEP DETERMINATION DEVICE FOR LEGGED MOBILE ROBOT

(54) 発明の名称: 脚式移動ロボットの制御装置および足跡決定装置



(57) Abstract: A control device and a footstep determination device for a legged mobile robot, wherein the landing position and landing direction of a foot (22) landing in the landing operation of the robot (1) such as a bipedal mobile robot are estimated and the target footstep route of the robot (1) is set up, future target landing position and target landing direction are determined based on the estimated landing position and landing direction and the target footstep route so that the actual footstep route (rows of landing positions and landing directions of the foot (22)) of the robot (1) near the target footstep route, the target gait pattern of the robot (1) is determined by using at least the determined target landing position and target landing direction, the operational control of the robot (1) is performed according to the target gait pattern, and when the target landing position and landing direction are determined, the mechanical restricting conditions of the robot (1) itself such as an interference between leg bodies and the restricting conditions in the target ZMP presence allowable range.

[続葉有]

ABSTRACT

A landing position/orientation of a foot (22) to be landed in a landing action of a robot (1) such as a bi-ped mobile robot or the like is estimated, and a desired footstep path for the robot (1) is set up. Based on the estimated landing position/orientation and the desired footstep path, a future desired landing position/orientation is determined in order to cause actual footsteps of the robot (1) (a sequence of landing positions/orientations of the foot (22)) to approach desired footsteps. Using at least the determined desired landing position/orientation, a desired gait for the robot (1) is determined, and the robot (1) is controlled in operation depending on the desired gait. For determining the desired landing position/orientation, mechanism-dependent limitations of the robot (1) such as an interference between the legs thereof, etc., and limiting conditions of an allowable range in which a desired ZMP can exist are taken into consideration.